

Green Lifting Sling WLL 2000 kg

Product code: FASC 2T | **Category:** Lifting Accessory, slings and lifting bands



Product images

L'AMBIENTE DEI PAESI	PORTATA SINGOLA NEL 2010					PORTATA MULTIPLO PER TRAMITE NEL 2010				
	AREA SUD	AREA CENTRALE	A-1*	A-2** A-3***	A-4***	AREA SUD	AREA CENTRALE	A-1**	A-2***	A-3***
16	1,0	0,9	3,0	1,4	3,0	1,4	1,0	3,0	3,0	3,0
40	2,0	1,6	4,0	2,8	2,0	2,0	2,2	3,0	3,0	3,0
56	3,0	2,4	6,0	4,2	3,0	4,2	3,0	3,4	2,4	3,0
72	4,0	3,2	8,0	5,4	4,0	5,4	4,0	4,0	3,2	3,0
88	5,0	4,0	10,0	6,6	5,0	6,6	5,0	4,6	4,0	3,0
104	6,0	4,8	12,0	7,8	6,0	7,8	6,0	5,6	4,8	3,0
120	7,0	5,6	14,0	9,0	7,0	9,0	6,8	6,0	5,6	3,0
136	8,0	6,4	16,0	10,2	8,0	10,2	8,0	6,8	6,4	3,0
152	9,0	7,2	18,0	11,4	9,0	11,4	9,0	7,6	7,2	3,0



Short description

Green Lifting Sling WLL 2000 kg

The green lifting slings WLL 2000 kg are available in different lengths to suit numerous industrial and logistics applications. Manufactured from high-strength polyester with a double-layer textile structure, they comply with EN 1492-1 and feature colour coding for immediate load capacity identification.

The indicated capacity refers to lifting in vertical configuration. The working load limit varies according to the lifting method and working angles.

- Available in various lengths
- Width: 60 mm
- Safety Factor: 7:1
- Colour coding compliant with EN 1492-1

Visit our [DISCOUNT price list](#).

Technical specifications

Weight	1 kg
Lunghezza	2 mt, 3 mt, 4 mt, 5 mt

Product variations

Variation name	Variation values	Variation SKU
Green Lifting Sling WLL 2000 kg - 2 mt	Lenght: 2 mt	0000000286
Green Lifting Sling WLL 2000 kg - 3 mt	Lenght: 3 mt	0000000287
Green Lifting Sling WLL 2000 kg - 4 mt	Lenght: 4 mt	0000000288
Green Lifting Sling WLL 2000 kg - 5 mt	Lenght: 5 mt	0000000289

Product description

Green Lifting Sling WLL 2000 kg - EN 1492-1

The green lifting sling with a WLL of 2000 kg is made of high-strength polyester, ensuring long-lasting durability and high reliability during lifting operations.

Compliant with EN 1492-1:2009, it is one of the most widely used lifting solutions thanks to its versatility and adaptability to a wide range of industrial, logistics, and construction applications.

The green colour, compliant with the standard colour coding system, allows immediate identification of the lifting capacity before use, reducing the risk of operational errors. The double-layer HT polyester construction provides excellent resistance to abrasion and wear during professional use.

Thanks to the 7:1 safety factor, these slings offer a wide safety margin, making them ideal for professional lifting operations with maximum reliability.

Warnings before use:

- Do not use on sharp edges without adequate protection.
- Do not use damaged, cut, or unlabeled slings.
- The indicated capacity refers to lifting in vertical configuration.

- The working load limit varies according to the lifting configuration and working angles.

Technical Specifications

- Working Load Limit (WLL): 2000 kg
- Material: High-strength polyester
- Structure: Double layer
- Safety Factor: 7:1
- Standard: EN 1492-1
- Sling Width: 60 mm
- Identification Colour: green

Why choose our slings?

Soltec lifting slings are manufactured according to EN 1492-1 and supplied with an identification label indicating capacity, material, safety factor, and manufacturer details.

Always check the integrity of the sling before use and use the product only according to the specified operating instructions.

On Soltecshop you can find a wide range of [professional lifting accessories](#) designed to meet every operational requirement with high standards of quality, reliability, and safety.

Do you need equipment for an industrial vehicle or a customised solution? Contact us for more information or visit the [Soltec](#) website.



Soltec Srl P.I. 01621900446
Italy: +39 0735 702346
France: +33 (0)1 89 53 25 34
Deutsch: +49 89 2620 25884
Spain: +34 936 421 546
Whatsapp: +39 351 68 17 340
Email: info@soltecshop.com
Via Valle Piana, 40
63074 San Benedetto del Tronto (AP) ITALY

