

SANGLES DE LEVAGE


SoltecShop.com

SANGLES DE LEVAGE

Flat web lifting slings

- Disponibles en différents modèles, longueurs et capacités de charge.
They are available in different models, lengths and load capacities
- Matériau : polyester HT.
Material: RS pro polyester.
- Facteur de sécurité: 7:1.
Safety factor: 7:1.

SANGLES DISPONIBLES – *Slings available*



CARACTÉRISTIQUES - *Features*

Extra-EU product

- Coloration/étiquetage: EN1492-1:2009.
Coloring/Labeling: EN1492-1:2009.
- Elles s'adaptent aux différentes exigences de levage et sont très résistantes à l'abrasion.
They are adaptable to different lifting needs and are highly abrasion-resistant.
- Conçues pour garantir des opérations de manutention sûres, fiables et conformes aux normes européennes. Le polyester haute résistance assure flexibilité, légèreté et protection des surfaces de chargement.
Designed to ensure safe, reliable handling operations in compliance with European standards. The high-strength polyester provides flexibility, lightness, and effective protection of the load surfaces.

MODÈLES DISPONIBLES

Available models

Modèle <i>Model</i>	Longueurs <i>Available lengths</i>	Largeur de sangle <i>Belt width</i>	 Capacité verticale <i>Vertical capacity</i>	 Capacité de boucle <i>Loop capacity</i>	 Capacité enroulée <7° <i>Hoop capacity <7°</i>
FASC_1T	2-3-4-5 m	50 mm	1 ton	0,8 ton	2 ton
FASC_2T	2-3-4-5 m	50 mm	2 ton	1,6 ton	4 ton
FASC_3T	2-3-4-5 m	75 mm	3 ton	2,4 ton	6 ton
FASC_4T	3 m	100 mm	4 ton	3,2 ton	8 ton
FASC_5T	3 m	150 cm	5 ton	4 ton	10 ton
FASC_6T	3 m – 6 m	150 mm	6 ton	4,8 ton	12 ton



SOLTEC SRL
Via Valle Piana, 40
63074 San Benedetto del Tronto
P.IVA/CF 01621900446 – SDI: KRRH6B9



+39 0735 702346



soltec@soltec.org



www.soltec.org



www.soltecshop.com